

# RAYZA RX544

## Lightweight Polyurethane Coated Index C Glove

### SPECIFICATION & CHARACTERISTICS

#### CODE

RX544

#### SIZE RANGE

6XS/112XL

#### PACKAGING

10 pairs/pack - 100 pairs/carton

#### PALM COATING

Silicone-free Polyurethane

#### LINING

Dyneema® Diamond Technology

#### CHARACTERISTICS

- Dyneema® yarn provides exceptional comfort
- Ultra-lightweight and dextrous - just like second skin.
- Touchscreen compatible
- Silicone-free polyurethane coating eliminates silicone contamination in manufacturing environments.
- Unique polyurethane coating provides excellent durability.
- Highly durable coating suitable for dry and slightly oily conditions.



### STANDARDS COMPLIANCE

#### EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
C = Cut (EN ISO 13997)	(Rating A-F)

**Notes:** Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

\*Gloves should not be used when working with serrated blades.



T: +44 (0)203 5000 723 E: info@stalsen.com

[www.stalsen.com](http://www.stalsen.com)

Rayza RX544 | Lightweight Polyurethane coated Cut Level C Glove - Datasheet

 **STALSEN®**  
KEEPING HANDS SAFE