

RAYZA RX544

Lightweight Polyurethane Coated Cut Level C Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX544

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Silicone-free Polyurethane

LINER

18 Gauge Dyneema® Diamond Technology

CHARACTERISTICS

- Dyneema® yarn provides exceptional comfort
- Ultra-lightweight and dextrous - just like second skin
- Touchscreen compatible
- Silicone-free polyurethane coating eliminates silicone contamination in manufacturing environments.
- Highly durable coating suitable for dry and slightly oily conditions
- Washable



STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
C = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: info@stalsen.com

www.stalsen.com

Rayza RX544 | Lightweight Polyurethane Coated Cut Level C Glove - Datasheet

 **STALSEN®**
KEEPING HANDS SAFE