

# INVOLITE IT918

## NBR Coated Precision Glove

### SPECIFICATION & CHARACTERISTICS

#### CODE

IT918

#### SIZE RANGE

6/XS - 11/XXL

#### PACKAGING

10 pairs/carton - 200 pairs/pack

#### PALM COATING

NBR

#### LINER

18 Gauge Knitted Nylon

### CHARACTERISTICS

- Outstanding dexterity and sensitivity
- Extremely comfortable liner – just like a second skin
- Offers remarkable grip
- Ideal for handling very small oily components.

### STANDARDS COMPLIANCE

#### EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

|                        |                         |
|------------------------|-------------------------|
| 4 = Abrasion           | (Performance Index 1-4) |
| 1 = Blade Cut* (Coup)  | (Performance Index 1-5) |
| 2 = Tear               | (Performance Index 1-4) |
| 1 = Puncture           | (Performance Index 1-4) |
| X = Cut (EN ISO 13997) | (Rating A-F)            |

**Notes:** Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

\*Gloves should not be used when working with serrated blades.



T: +44 (0) 1394 447090 E: [info@stalsen.com](mailto:info@stalsen.com) [www.stalsen.com](http://www.stalsen.com)

Involute IT918 | NBR Coated Precision Glove - Datasheet

 **STALSEN**<sup>®</sup>  
KEEPING HANDS SAFE