

RAYZA RX328

ESD Polyurethane Coated Cut Level B Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX328

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Polyurethane

LINER

15 Gauge HPPE with carbon

CHARACTERISTICS

- High quality Japanese HPPE
- High durable polyurethane coating
- Suitable for dry conditions involving electronic components

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
3 = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
B = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.

EN16350:2014 Electrostatic properties

This standard prescribes the following test conditions and minimum requirements for the electrostatic properties of protective gloves:

- The contact resistance of a glove must be less than 100 megaohms ($R_v < 1.0 \times 10^8 \Omega$)
- DIN EN 1149-2:1997 regulates contact resistance
- The atmosphere during testing for contact resistance must constitute an ambient temperature of $23^\circ\text{C} (\pm 1^\circ\text{C})$ and have relative humidity of $25\% (\pm 5\%)$
- Five tests will be conducted and each measurement must be within the threshold values



4342B



T: + 44 (0) 1394 447090 E: info@stalsen.com

www.stalsen.com

Rayza RX328 | ESD Polyurethane Coated Cut Level B Glove - Datasheet

 **STALSEN**[®]
KEEPING HANDS SAFE