

Rayza RX518

Cut level D Lower Arm Protection

SPECIFICATION AND CHARACTERISTICS

CODE

RX518

SIZE

18"

EMBALAGEM

20 pairs/packs - 100 pairs/carton

LINING

HPPE

CHARACTERISTICS

- High quality Japanese HPPE liner
- Non-slip top to prevent movement
- Thumbhole for enhanced comfort
- Seamless, breathable material
- Washable

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

2 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
X = Puncture	(Performance Index 1-4)
D = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: +44 (0)203 5000 723 E: info@stalsen.com www.stalsen.com

Rayza RX518 | Lower Arm Protection - Datasheet

 **STALSEN**[®]
KEEPING HANDS SAFE