

# RAYZA RX335

## Polyurethane Coated Cut Level B Glove

### SPECIFICATION & CHARACTERISTICS

#### CODE

RX335

#### SIZE RANGE

6/XS - 11/2XL

#### PACKAGING

10 pairs/pack - 100 pairs/carton

#### PALM COATING

Polyurethane

#### LINER

15 Gauge seamless premium grade HPPE

#### CHARACTERISTICS

- High quality Japanese HPPE
- High spandex content and a seamless finish ensures exceptional comfort
- 15-gauge liner offers superior dexterity
- Excellent grip in dry or slightly oily conditions
- Breathable back
- Washable



### STANDARDS COMPLIANCE

#### EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
3 = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
B = Cut (EN ISO 13997)	(Rating A-F)

**Notes:** Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

\*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: [info@stalsen.com](mailto:info@stalsen.com) [www.stalsen.com](http://www.stalsen.com)

Rayza RX335 | Polyurethane Coated Cut Level B Glove - Datasheet

 **STALSEN**<sup>®</sup>  
KEEPING HANDS SAFE