

# RAYZA RXS545

## Polyurethane Coated Cut Level D Glove

### SPECIFICATION & CHARACTERISTICS

#### CODE

RXS545

#### SIZE RANGE

16/XS-11/XXL

#### PACKAGING

10 pairs/pack - 10 packs/case

#### PALM COATING

Polyurethane

#### LINER

Tsunooga™ high strength, high modulus polyethylene fibers

#### CHARACTERISTICS

- High quality Japanese HPPE
- Excellent mechanical resistance
- Seamless liner with anti-bacterial and moisture-wicking properties
- Breathable back
- Excellent for dry and slightly oily conditions
- Providing a high level of cut resistance
- Washable



### STANDARDS COMPLIANCE

#### EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
3 = Puncture	(Performance Index 1-4)
D = Cut (EN ISO 13997)	(Rating A-F)

**Notes:** Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

\*Gloves should not be used when working with serrated blades.



T: +44 (0)203 5000 723 E: [info@stalsen.com](mailto:info@stalsen.com) [www.stalsen.com](http://www.stalsen.com)

Rayza RXS545 | Polyurethane Coated Cut Level D Glove - Datasheet

 **STALSEN**<sup>®</sup>  
KEEPING HANDS SAFE