

RAYZA RX432

Lightweight Polyurethane Coated Cut Level B Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX432

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Polyurethane

LINER

18 Gauge Tsunooga™ high strength, high modulus polyurethane fibres

CHARACTERISTICS

- Ultra-lightweight liner provides exceptional comfort and dexterity
- Seamless liner with anti-bacterial and moisture-wicking properties
- Excellent mechanical resistance
- Offers excellent fingertip precision
- Breathable back
- Washable
- Ideal for dry or slightly oily conditions



STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

| | |
|------------------------|-------------------------|
| 3 = Abrasion | (Performance Index 1-4) |
| 4 = Blade Cut* (Coup) | (Performance Index 1-5) |
| 3 = Tear | (Performance Index 1-4) |
| 1 = Puncture | (Performance Index 1-4) |
| B = Cut (EN ISO 13997) | (Rating A-F) |

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: info@stalsen.com

www.stalsen.com

Rayza RX432 | Lightweight Polyurethane Coated Cut Level B Glove - Datasheet

 **STALSEN**[®]
KEEPING HANDS SAFE