

RAYZA RX553

Polyurethane Coated Cut Level E Thermal Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX553

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Silicone-free Polyurethane

LINER

15 Gauge HPPE with thermal polyester

CHARACTERISTICS

- High quality cut resistant liner with outstanding mechanical performance.
- Lightweight thermal liner provides exceptional comfort, dexterity and insulation
- Innovative insulating yarn retains heat, suitable for dry and cold conditions
- Touchscreen compatibility

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
E = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.

EN511: Resistance to the cold

Specifies a glove's performance in protection against the cold. This cold can be linked to weather conditions or to industrial activity.

X = Convective cold	(Performance Index 0-4)
1 = Contact cold	(Performance Index 0-4)
X = Water penetration	(1 = Pass/0 = Fail)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.



T: + 44 (0) 1394 447090 E: info@stalsen.com

www.stalsen.com

Rayza RX553 | Polyurethane Coated Cut Level E Thermal Glove - Datasheet

 **STALSEN**[®]
KEEPING HANDS SAFE