

RAYZA RX562

Ultra-lightweight Polyurethane Cut Level F Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX562

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Polyurethane

LINER

21 Gauge HPPE

CHARACTERISTICS

- New generation cut resistant liner with maximum cut mechanical performance.
- Ultra-lightweight liner provides exceptional dexterity, touch sensitivity and comfort.
- A highly breathable yet tough polyurethane coating, suitable for dry or slightly oily environments.
- Touchscreen compatibility

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
F = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: info@stalsen.com www.stalsen.com

Rayza RX562 | Ultra-lightweight Polyurethane Coated Cut Level F Glove - Datasheet

 **STALSEN**
KEEPING HANDS SAFE