

INVOTOUCH IT950

Polyurethane Coated Glove

SPECIFICATION & CHARACTERISTICS

CODE

IT950

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 200 pairs/carton

PALM COATING

Silicone-free Polyurethane

LINER

15 Gauge nylon

CHARACTERISTICS

- 15 gauge ideal for precision jobs in dry environments
- Combines comfort, dexterity and sensitivity
- Durable PU coating
- Silicone-free polyurethane coating eliminates silicone contamination in manufacturing environments
- Washable

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
1 = Blade Cut* (Coup)	(Performance Index 1-5)
2 = Tear	(Performance Index 1-4)
1 = Puncture	(Performance Index 1-4)
A = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: info@stalsen.com www.stalsen.com

Invotouch IT950 | Polyurethane Coated Glove - Datasheet

 **STALSEN**[®]
KEEPING HANDS SAFE