

RAYZA RX550

Lightweight Uncoated Cut Level E Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX550

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Uncoated

LINER

18 Gauge HPPE

CHARACTERISTICS

- High quality cut resistant liner with outstanding mechanical performance.
- Ultra-lightweight 18-gauge liner ensures high levels of comfort and dexterity - just like a second skin
- Touchscreen compatibility
- Ideal for working in clean, dry environments
- Washable

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

2 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
E = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: info@stalsen.com www.stalsen.com

Rayza RX550 | Lightweight uncoated Cut Level E Glove - Datasheet

 **STALSEN®**
KEEPING HANDS SAFE