

# RAYZA RX567

## Double Dipped Nitrile Cut Level E Thermal Glove

### SPECIFICATION & CHARACTERISTICS

#### CODE

RX567

#### SIZE RANGE

7/S - 12/3XL

#### PACKAGING

10 pairs/pack - 100 pairs/carton

#### PALM COATING

Black Textured Nitrile

#### LINER

18-Gauge HPPE with fleece liner

#### CHARACTERISTICS

- Fleece liner provides ultimate warmth and comfort without inhibiting flexibility.
- Extended cuff for enhanced protection in the wrist area.
- A lightweight lining that ensures high levels of protection as well as comfort and flexibility.
- A fully coated nitrile barrier ensuring high performance against liquid penetration across the whole glove.
- A textured nitrile coating for enhanced grip in wet or oily conditions.



### STANDARDS COMPLIANCE

#### EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

|                        |                         |
|------------------------|-------------------------|
| 4 = Abrasion           | (Performance Index 1-4) |
| X = Blade Cut* (Coup)  | (Performance Index 1-5) |
| 4 = Tear               | (Performance Index 1-4) |
| 2 = Puncture           | (Performance Index 1-4) |
| E = Cut (EN ISO 13997) | (Rating A-F)            |

**Notes:** Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

\*Gloves should not be used when working with serrated blades.

#### EN511: Resistance To The Cold

Specifies a glove's performance in protection against the cold. This cold can be linked to weather conditions or to industrial activity.

|                       |                         |
|-----------------------|-------------------------|
| X = Convective cold   | (Performance Index 0-4) |
| 1 = Contact cold      | (Performance Index 0-4) |
| X = Water penetration | (1 = Pass/0 = Fail)     |

**Notes:** Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.



T: + 44 (0) 1394 447090 E: [info@stalsen.com](mailto:info@stalsen.com)

[www.stalsen.com](http://www.stalsen.com)

Rayza RX567 | Double Dipped Nitrile Cut Level E Thermal Glove - Datasheet

**STALSEN**  
KEEPING HANDS SAFE