

RAYZA RX522

Lightweight Cut Level E Lower Arm Protection

SPECIFICATION & CHARACTERISTICS

CODE

RX522

SIZE RANGE

450mm

PACKAGING

10 pairs/pack - 50 sleeves/carton

LINER

18 Gauge HPPE

CHARACTERISTICS

- Advanced 18-gauge liner
- Ultra lightweight and highly breathable
- Exceptional levels of comfort, just like second skin
- A velcro top cuff to stop the sleeve from slipping down the arm
- Thin nylon thumb slot to prevent the sleeve from riding up the arm and exposing vital arteries
- Does not restrict dexterity and movement when used with a glove

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

2 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
X = Puncture	(Performance Index 1-4)
E = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: info@stalsen.com www.stalsen.com

Rayza RX522 | Lightweight Cut Level E Lower Arm Protection - Datasheet

 **STALSEN®**
KEEPING HANDS SAFE