

MAGMA MX262

Hide Leather Welder's Gauntlet

SPECIFICATION & CHARACTERISTICS

CODE

MX251

SIZE RANGE

9/L - 10/XL

PACKAGING

10 pairs/pack - 60 pairs/carton

LEATHER

Top grade cow split

LINER

Cotton fleece at palm

CHARACTERISTICS

- Top grade cow grain leather
- Wide fit for ease of donning
- Increased length for extra protection
- Superbly soft and supple leather
- Pigment free to retain flexibility
- Heat resistant Kevlar stitching

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

2 = Abrasion	(Performance Index 1-4)
1 = Blade Cut* (Coup)	(Performance Index 1-5)
1 = Tear	(Performance Index 1-4)
1 = Puncture	(Performance Index 1-4)
X = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.

EN407: 2020 Thermal risks (heat and/or fire)

This standard specifies thermal performance for protective gloves against heat and/or fire. The table below indicates the glove's resistance to:

X = Flammability	(Performance Index 1-4)
1 = Contact heat	(Performance Index 1-5)
X = Convective heat	(Performance Index 1-4)
X = Radiant heat	(Performance Index 1-4)
X = Small splashes of molten metal	(Performance Index 1-4)
X = Large splashes of molten metal	(Performance Index 1-4)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

EN12477

Manual Metal Welding Hazards

Rating: Type A



T: +44 (0)203 5000 723 E: info@stalsen.com

www.stalsen.com

Magma MX262 | Hide Leather Welder's Gauntlet - Datasheet

 **STALSEN**[®]
KEEPING HANDS SAFE