

MAGMA MX267

Hide Leather Welder's Gauntlet

SPECIFICATION AND CHARACTERISTICS

CODE

MX267

SIZE

9-11

PACKAGING

10 pairs/packs - 60 pairs/carton

LEATHER

Top grade sheep grain

STITCHING

Heat resistant Kevlar

CHARACTERISTICS

- Top grade sheep grain leather
- Wide fit for ease of donning
- Heat resistant Kevlar stitching
- Thumb and crotch reinforcement
- Superbly soft and supple leather

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

1	= Abrasion	(Performance Index 1-4)
1	= Blade Cut* (Coup)	(Performance Index 1-5)
1	= Tear	(Performance Index 1-4)
2	= Puncture	(Performance Index 1-4)
X	= Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.

EN407: 2020 Thermal risks (heat and/or fire)

This standard specifies thermal performance for protective gloves against heat and/or fire. The table below indicates the glove's resistance to:

4	= Flammability	(Performance Index 1-4)
1	= Contact heat	(Performance Index 1-5)
2	= Convective heat	(Performance Index 1-4)
X	= Radiant heat	(Performance Index 1-4)
4	= Small splashes of molten metal	(Performance Index 1-4)
X	= Large splashes of molten metal	(Performance Index 1-4)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

EN12477

Manual Metal Welding Hazards

Rating: Type A



T: +44 (0)203 5000 723 E: info@stalsen.com www.stalsen.com

Magma MX267 | Hide Leather Welder's Gauntlet - Datasheet

 **STALSEN®**
KEEPING HANDS SAFE