

RAYZA RX335

Polyurethane Coated Cut Level B Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX335

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Polyurethane

LINER

15 Gauge seamless premium grade HPPE

CHARACTERISTICS

- High quality Japanese HPPE
- High spandex content and a seamless finish ensures exceptional comfort
- 15-gauge liner offers superior dexterity
- Excellent grip in dry or slightly oily conditions
- Breathable back
- Washable

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
3 = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
B = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: info@stalsen.com www.stalsen.com

Rayza RX335 | Polyurethane Coated Cut Level B Glove - Datasheet

 **STALSEN**
KEEPING HANDS SAFE