

RAYZA RX565

Double Dipped Nitrile Cut Level E Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX565

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Textured Nitrile

LINER

18 Gauge HPPE

CHARACTERISTICS

- Ultra-lightweight liner provides high levels of comfort and dexterity
- Extended cuff for enhanced protection in the wrist area
- A fully coated nitrile barrier ensures high performance against liquid penetration across the glove
- A textured nitrile coating for enhanced grip and a degree of oil resistance

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
E = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: info@stalsen.com www.stalsen.com

Rayza RX565 | Double Dipped Nitrile Cut Level E Glove - Datasheet

 **STALSEN**
KEEPING HANDS SAFE