

RAYZA RX564

Lightweight 3/4 Dipped Nitrile Coated Cut Level E Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX564

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Nitrile

LINER

18 Gauge HPPE with Tugsten, Nylon and Spandex

CHARACTERISTICS

- High quality cut resistant liner with outstanding mechanical performance.
- Ultra-lightweight liner provides exceptional comfort and dexterity - just like a second skin
- Highly durable coating offers outstanding grip and is long-lasting in abrasive environments
- Touchscreen compatible
- No steel or glass fibre in the liner
- Silicone-free polyurethane coating eliminates silicone contamination in manufacturing environments.
- Heavy-duty coating suitable for dry and oily conditions

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
4 = Puncture	(Performance Index 1-4)
E = Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



T: + 44 (0) 1394 447090 E: info@stalsen.com www.stalsen.com

Rayza RX564 | Lightweight 3/4 Dipped Nitrile Coated Cut Level E Glove - Datasheet

 **STALSEN**[®]
KEEPING HANDS SAFE