

RAYZA RX557

NBR Coated Cut Level E Thermal Glove

SPECIFICATION & CHARACTERISTICS

CODE

RX557

SIZE RANGE

6/XS - 12/3XL

PACKAGING

10 pairs/pack - 100 pairs/carton

PALM COATING

Nitrile

LINER

18 Gauge HPPE

CHARACTERISTICS

- High quality cut resistant liner with outstanding mechanical performance.
- Ultra-lightweight liner provides exceptional comfort and dexterity
- Highly durable coating offers outstanding grip and is long-lasting in highly abrasive environments
- Heavy-duty coating suitable for dry and oily conditions

STANDARDS COMPLIANCE

EN388:2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4	= Abrasion	(Performance Index 1-4)
X	= Blade Cut* (Coup)	(Performance Index 1-5)
4	= Tear	(Performance Index 1-4)
3	= Puncture	(Performance Index 1-4)
E	= Cut (EN ISO 13997)	(Rating A-F)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.

EN511:2006 Resistance To Cold

Specifies a glove's performance in protection against the cold. This cold can be linked to weather conditions or to industrial activity.

X	= Convective cold	(Performance Index 0-4)
2	= Contact cold	(Performance Index 0-4)
X	= Water penetration	(1 = Pass / 0 = Fail)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.



T: + 44 (0) 1394 447090 E: info@stalsen.com www.stalsen.com

Rayza RX557 | NBR Coated Cut Level E Thermal Glove - Datasheet

STALSEN
KEEPING HANDS SAFE