

RAYZA RX590

Waterproof Foam Nitrile Coated Impact Resistant Cut Level F glove

SPECIFICATION & CHARACTERISTICS

CODE

RX590

SIZE RANGE

6/XS - 11/2XL

PACKAGING

10 pairs/pack - 50 pairs/carton

PALM COATING

Foam Nitrile

LINER

13 Gauge HPPE with waterproof lining

CHARACTERISTICS

- New generation cut resistant liner with maximum cut mechanical performance
- Waterproof liner ensures hands are kept dry in wet conditions
- Touchscreen compatibility
- Foam nitrile palm coating suitable for oily and wet conditions
- Moulded impact pads to increase comfort and flexibility
- High-visibility impact pads increase safety

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
F = Cut (EN ISO 13997)	(Rating A-F)
P = Impact Resistance	(P for passed)

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.

ANSI/ISEA 138:2019 Impact Protection

Testing of knuckles as well as finger protection for impact.



T: + 44 (0) 1394 447090 **E:** info@stalsen.com **www.stalsen.com**

Rayza RX590 | Waterproof Foam Nitrile Coated Impact Resistant Cut Level F glove - Datasheet

STALSEN
KEEPING HANDS SAFE