

STALGrip ST895-Bla

Black Premium Nitrile Powder-free Grip Glove

SPECIFICATION

CODE

ST895

SIZE RANGE

6/XS -11/2XL

PACKAGING

100 gloves/box - 10 boxes/carton

MATERIAL

Nitrile

THICKNESS

6mil

GLOVE LENGTH

240mm

ACCEPTABLE QUALITY LEVEL (AQL)

1.5

TENSILE STRENGTH (AFTER AGING)

26MPa

ULTIMATE ELONGATION (AFTER AGING)

400%

AVAILABLE COLOURS

Red, green, yellow, blue, orange



T: +44 (0)1394 447090

E: info@stalsen.com

www.stalsen.com

STALGrip ST895-Bla | Black premium nitrile powder-free grip glove - Datasheet

CHARACTERISTICS

- Exceptional mechanical strength
- Premium nitrile formulation
- Raised textured grip pattern for excellent grip power
- Suitable wet and dry grip applications
- Excellent resistance to hydrocarbons, fats and solvents
- Beaded cuff to prevent liquid roll-off
- Designed for easy donning and doffing
- Good chemical splash resistance
- Extended cuff for increased protection
- Shelf life of 3 years with no substantial degradation of physical properties
- Ambidextrous
- Free of latex proteins
- Suitable for food contact



STANDARDS COMPLIANCE

EN ISO 374-5:2016/Micro Organism Risks

The 'micro-organism' pictogram is to be used when the glove conforms to at least a performance level 2 for the Penetration test.



EN ISO 374-5: 2016 Resistance to Bacteria and Fungi

The penetration resistance has been assessed under laboratory conditions and relates only to the tested specimen.

Resistance to Bacteria and Fungi - Pass

Resistance to Virus - Pass

EN ISO 374-1:2016 + A1:2018/Type B

Penetration

Formaldehyde 37% (T)	Level 6 (>480 minutes)
Hydrogen Peroxide 30% (P)	Level 2 (>30 minutes)
Sodium Hydroxide 40% (K)	Level 6 (>480 minutes)
4% Chlorhexidine	Level 6 (>480 minutes)
105 Formalin	Level 2 (>30 minutes)
4% Gluterdehyde	Level 6 (>480 minutes)
33% Formaldehyde	Level 2 (>30 minutes)
3% Hydrogen Peroxide	Level 6 (>480 minutes)



STALSEN®
KEEPING HANDS SAFE